


SANIT WC control encoded radio signal mains supply



Item number	Product description
05.390.00..0000	<p>WC control system using encoded radio signals for accessible construction as per DIN 18040</p> <p>Finishing set with mains supply 230V AC/6V DC</p> <p>WC flush system for manual remote flush actuation via arm support rails with wireless push button, for concealed cisterns with a small access opening (from year of construction 2014) CC-121-S-FO-2V-2C, CC-122-S-UO-2V-2C and CC-150-S-UO-2V-2C</p> <p>Contents:</p> <ul style="list-style-type: none"> - low-voltage motor for lifting device and control electronics with bracket - radio receiver module - power supply 230V AC/6V DC <p>Parameters:</p> <ul style="list-style-type: none"> - automatic interval flush factory set to 24 h - floating output, power rating 42V/0.5 A, pulse duration 0.5 sec. - connection with up to 32 radio transmitters possible - manual single flush also possible - flush volume from 4.5-9 l, depending on the concealed cistern model - with error-safe plug connections - power supply for installation outside the concealed cistern - designed for a maximum distance of 1.7 m between the concealed cistern and the power supply unit <p>Settings on low-voltage motor can be adjusted via service and maintenance remote control DO-5.1 S*): 0-108 h interval flush after last electronic flush</p> <ul style="list-style-type: none"> - frequency: 868.4 MHz (ISM range, no registration required, not subject to fees) - transmission security by means of an automatic encoding procedure - power output: < 5 mW, range 10 m, ambient temperature -20°C to 65°C - radio receiver module with additional output for freely definable function *) to be ordered separately <p>Accessories:</p> <ul style="list-style-type: none"> - concealed installation module code no. 03.933.00..0000 - radio transmitter code no. 03.162.00..0000 - service and maintenance remote control code no. 03.806.00..0000