


91.910.01..0000

## SANIT Cistern 926 pneumatic 1V white



### Item number

91.910.01..0000

### Product description

Cistern 926 with WC push button, single flush, for remote pneumatic flush actuation

Low-level for in-wall installation, flush volume adjustable from 6-9 l, factory set to 6 l, fully insulated, 3-side connection and low noise fill valve, cistern dimensions w/h/d: 442 x 366 x 150 mm, distance middle water inlet cistern/middle flush pipe outlet 485 mm, fixation of cistern middle/middle 240 mm, flush pipe length from upper edge of wall to end of flush pipe 155-263 mm, consisting of: cistern 926, angle valve G 1/2 and chromed connection pipe, flush pipe bend with rubber joint, pneumatic single flush WC push button, plastic, white, for brick and dry wall installation, w/h 120 x 114 mm, height above tiles 31 mm, minimum installation depth from wall covering to back of roughing-in box 65 mm, with pneumatic push button unit, single flush pneumatic lift device, roughing-in box with protection box, single flush pneumatic hose - 2.35 m, empty pipe set with 1.7 m pull cord, installation instructions and fastenings, packed in a box An additional flush operation by the push button integrated in the cistern cover is not possible.

Accessories for flush pipe extension:

- extension pipe